

IP CCTV / Professional IP cameras / Uniview - Uniarch / Speed Domes

UV-UHO-P2S-M33F34

Uniarch



Features

- Uniarch
- WiFi PTZ IP Camera
- 1/2.8" Progressive Scan CMOS
- 3 Megapixel
- Lens 2.8 mm panoramic and 4 mm PTZ
- 0 Lux
- IR Range 30 m
- Compression Ultra265/H.265/H.264
- Weatherproof IP66
- RJ-45 10/100 BaseTX
- Wifi IEEE802.11b/g/n/ax
- IR Cut
- Built-in microphone
- DWDR
- MicroSD 512 GB

Specifications

Brand	Uniarch
Image sensor	1/2.8" Progressive Scan CMOS
Maximum resolution	3 Megapixel (2304x1296)
Fixed lens	2.8 mm
PTZ Lens	4.0 mm
Main Stream rate	Panoramic / PTZ: 3MP (2304x1296)@15fps; 2MP (1920x1080)@15fps; 720P (1280x720)@15fps
Extra Stream rate	Panoramic / PTZ: 640x360@15fps; 2CIF (704x288)@15fps; CIF (352x288)@15fps
Video compression	Ultra 265, H.265, H.264, MJPEG
Minimum illumination	Colour: 0.003 lux (F1.6 AGC ON) 0 lux with IR on
Infrared range	Overview: 10 m PTZ: 30 m
Detection functions	Motion Detection, Ultra Motion Detection, Audio Detection, Tamper Alarm.
Image improvements	DWDR, BLC, HLC, AGC, 2D/3D-NR, Motion detection, ROI, Privacy Mask
Day / Night	Mechanical ICR filter
Internal memory	MicroSD card, Max 512 GB
Alarms	Does not have
Audio	Built-in microphone and speaker
Audio Compression	G.711U, G.711A
Wi-Fi	IEEE802.11b/g/n/ax
Wi-Fi frequency range	2.4 GHz ~ 2.4835 GHz
Remote access	Web Browser, CMS Software (EZStation), Smartphone (UNV-LINK, UNV-LINK Pro, Uniarch APP)
Power	DC 12V / 10W
Temp. operation	-30° C ~ 60° C
Degree of protection	Waterproof IP66, overvoltage 4KV
Dimensions	Ø117(W) x 117(D) x 202(H) mm

Weight

610 g
